

NAME

rrdlist – List directories and rrd databases.

SYNOPSIS

rrdtool list [**--daemon**|**-d** *address*] [**--noflush**|**-F**] [**--recursive**|**-r**] *path*

DESCRIPTION

The **list** function provides an 'ls-like' interface for traversing and listing the rrd database tree.

When using the **--daemon** option, the **list** function connects to rrdcached, the RRD caching daemon, and issues a "list" command for the given path.

path The path (starting with '/') with '/' being the rrdcached base_dir.

--daemon|**-d** *address*

Address of the rrdcached daemon. If not specified, the RRDCACHED_ADDRESS environment variable must be set (see below). For a list of accepted formats, see the **-I** option in the rrdcached manual.

```
rrdtool list --daemon 127.0.0.1:42218 /cluster/nodes/node1
```

--noflush|**-F**

When using a daemon, rrdtool list will usually flush its cache to the disk before performing operations. This option disables cache flushing.

--recursive|**-r**

Make the list of rrd databases recursive.

ENVIRONMENT VARIABLES

The following environment variables may be used to change the behavior of rrdtool list:

RRDCACHED_ADDRESS

If this environment variable is set it will have the same effect as specifying the **--daemon** option on the command line. If both are present, the command line argument takes precedence.

AUTHOR

Sebastien Dugue <sebastien.dugue@atos.net>